



cod.	Ø	pz/pcs	C	ØG	sp	R	bullone	cusc	binario	portata	CodTek
400.40	40	12	16	Ø33	12	4,5	M8x30	1	-	60 kg.	ARU040015ZB
400.50	50	12	16	Ø40	13	4,5	M8x30	1	-	80 kg.	ARU040001ZB
400.60/10	60/10	12	24	Ø48	17	5,3	M10x45	1	-	100 kg.	ARU040002ZB
400.60/16	60/16	12	24	Ø48	17	8,3	M10x45	1	902-904.16	100 kg.	ARU040016ZB
400.60/20	60/20	12	24	Ø50	17	10,3	M10x45	1	902-904.20	100 kg.	ARU040017ZB
400.70/16	70/16	6	33	Ø54	20	8,3	M14x70	1	902-904.16	190 kg.	ARU040003ZB
400.80/16	80/16	6	33	Ø64	20	8,3	M14x70	1	902-904.16	200 kg.	ARU040004ZB
400.80/20	80/20	6	33	Ø59	24	10,3	M14x70	1	902-904.20	200 kg.	ARU040005ZB
400.90/16	90/16	6	33	Ø74	21	8,3	M14x70	1	902-904.20	210 kg.	ARU040006ZB
400.90/20	90/20	6	33	Ø69	24	10,3	M14x70	1	902-904.20	210 kg.	ARU040007ZB
400.100/16	100/16	6	33	Ø84	21	8,3	M14x70	1	902-904.16	230 kg.	ARU040008ZB
400.100/20	100/20	6	33	Ø79	24	10,3	M14x70	1	902-904.20	230 kg.	ARU040009ZB
400.120	120	4	33	Ø99	24	10,3	M14x70	1	902-904.20	250 kg.	ARU040010ZB
400.140	140	4	43	Ø117	24	10,3	M16x70	1	902-904.20	280 kg.	ARU040011ZB
400.160	160	2	43	Ø137	25	10,3	M16x70	1	902-904.20	300 kg.	ARU040012ZB
400.200	200	2	43	Ø177	25	10,3	M16x70	1	902-904.20	340 kg.	ARU040013ZB



Sliding gates accessories



Galvanized steel components



- Components to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.  
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Araldo's property. All uses not expressly authorized by the company will be prosecuted.

