



cod.	Ø	pz/pcs	A	B	C	D	ØF	I	H	ØG	sp	R	cusc	binario	portata	CodTek
425IX.80/16	80/16	4	135	12	33	17	Ø9	110	49	Ø64	20	8,3	1	902IX.16	200 kg.	ARU042502IX
425IX.80/20	80/20	6	135	12	33	17	Ø9	110	49	Ø59	24	10,3	1	902IX-904IX.20	200 kg.	ARU042503IX
425IX.90/20	90/20	6	155	9	33	18	Ø9	130	61	Ø69	24	10,3	1	902IX-904IX.20	210 kg.	ARU042505IX
425IX.100/20	100/20	6	155	14	33	18	Ø9	130	66	Ø79	24	10,3	1	902IX-904IX.20	230 kg.	ARU042507IX
425IX.120	120	6	185	14	32	20	Ø9	155	84	Ø99	24	10,3	1	902IX-904IX.20	250 kg.	ARU042508IX



Sliding gates accessories



Stainless steel components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

