



cod.	Ø	pz/pcs	A	B	C	D	ØF	I	H	ØG	sp	R	cusc	binario	portata	CodTek
425NYIX.80/16	80/16	6	135	12	33	17	Ø9	110	49	Ø64	24	8,3	1	902IX.16	60 kg.	ARU042502NYIX
425NYIX.80/20	80/20	6	135	12	33	17	Ø9	110	49	Ø59	24	10,3	1	902IX-904IX.20	70 kg.	ARU042503NYIX
425NYIX.100/20	100/20	6	155	14	33	18	Ø9	130	66	Ø79	24	10,3	1	902IX-904IX.21	80 kg.	ARU042507NYIX



Sliding gates accessories



Stainless steel/nylon components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Check the product every 6/12 months.
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.
All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Araldo's property. All uses not expressly authorized by the company will be prosecuted.

