



cod.	Ø	pz/pcs	C	E	ØG	L	sp	CH	K	bullone	cusc	binario	portata	CodTek
441.100	100	4	33	43	Ø75	4	28	Es.27	8	M18x60	2	906	560 kg.	ARU044105ZB
441.120	120	4	33	43	Ø95	4	28	Es.27	8	M18x60	2	906	580 kg.	ARU044106ZB
441.140	140	4	43	53	Ø115	4	32	Es.30	9	M20x70	2	906	920 kg.	ARU044101ZB
441.140x80	140 Tub. 80	4	72	-	Ø115	4	32	Es.30	9	M20x90	2	906	920 kg.	ARU044107ZB
441.160	160	2	43	53	Ø135	4	32	Es.30	9	M20x70	2	906	940 kg.	ARU044102ZB
441.160x80	160 Tub. 80	2	72	-	Ø135	4	32	Es.30	9	M20x90	2	906	940 kg.	ARU044108ZB
441.200	200	2	43	53	Ø175	4	32	Es.30	9	M20x70	2	906	980 kg.	ARU044103ZB
441.200x80	200 Tub. 80	2	72	-	Ø175	4	32	Es.30	9	M20x90	2	906	980 kg.	ARU044109ZB
441.250	250	2	73	-	Ø213	4	48	Es.36	11	M24x100	2	906	1450 kg.	ARU044104ZB



Sliding gates accessories



Galvanized steel components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Lubricate all parts in contact with grease (every 6 months). In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

