



| cod. | Ø | pz/pcs | C | E | ØG | sp | CH | K | bullone | cusc | binario | portata | CodTek |
|------------|-------------|--------|----|----|------|----|-------|----|---------|------|---------|----------|-------------|
| 442.100 | 100 | 4 | 33 | 43 | Ø77 | 28 | Es.27 | 8 | M18x60 | 2 | 906 | 560 kg. | ARU044205ZB |
| 442.120 | 120 | 4 | 33 | 43 | Ø97 | 28 | Es.27 | 8 | M18x60 | 2 | 906 | 580 kg. | ARU044206ZB |
| 442.140 | 140 | 4 | 43 | 53 | Ø117 | 32 | Es.30 | 9 | M20x70 | 2 | 906 | 920 kg. | ARU044201ZB |
| 442.140x80 | 140 Tub. 80 | 4 | 72 | - | Ø117 | 32 | Es.30 | 9 | M20x90 | 2 | 906 | 920 kg. | ARU044207ZB |
| 442.160 | 160 | 2 | 43 | 53 | Ø137 | 32 | Es.30 | 9 | M20x70 | 2 | 906 | 940 kg. | ARU044202ZB |
| 442.160x80 | 160 Tub. 80 | 2 | 72 | - | Ø137 | 32 | Es.30 | 9 | M20x90 | 2 | 906 | 940 kg. | ARU044208ZB |
| 442.200 | 200 | 2 | 43 | 53 | Ø177 | 32 | Es.30 | 9 | M20x70 | 2 | 906 | 980 kg. | ARU044203ZB |
| 442.200x80 | 200 Tub. 80 | 2 | 72 | - | Ø177 | 32 | Es.30 | 9 | M20x90 | 2 | 906 | 980 kg. | ARU044209ZB |
| 442.250 | 250 | 2 | 73 | - | Ø217 | 48 | Es.36 | 11 | M24x100 | 2 | 906 | 1450 kg. | ARU044204ZB |



Sliding gates accessories



Galvanized steel components



- Components to weld and to fix
- Adequately strengthen the areas anchoring the door and/or structure / frame.



Lubricate all parts in contact with grease (every 6 months) .
In case of anomalies, prevent the usage of the hinge and the installed product must be checked by professional personnel.



Responsibly dispose of the product and of its packaging respecting the local legislations of the Country of installation.

The company reserves the right to make technical as well as aesthetic changes without previous notice.

All responsibility due to an inappropriate use of the product is declined.

All drawings, photos, trademarks, logos, are of exclusive Combi Arialdo's property. All uses not expressly authorized by the company will be prosecuted.

